

SRS Subwoofer



SRS Subwoofer

The SRS addresses the need for high output subwoofers with minimal size vent openings, offering improved integration, with a focus on Large Micro LED Display installations.

The SRS's highly efficient dual 10-inch woofers, built in an optimized transmission line, results in articulated bass with superior dynamics and accurate timbre, making it the perfect solution for the ultimate Music and Movie reproduction within large residential and theater spaces.

The Regenerative Transmission Line®

Regenerative Transmission Line® designs yielded the unique combination of high sensitivity, high output, and low distortion with the uniform and extended response we required. The result is extraordinary power and punch combined with a remarkable level of speed, tunefulness, and realism.

SRS Specifications

All specifications are subject to change at any time to improve the product.

- **Number of required amplifier channels: 1**
- **Frequency response:** 18Hz – 125 Hz \pm 3dB / -10dB at 15Hz
- **Impedance:** 4 Ω
- **Sensitivity:** 96 dB / 2.83V / 1m
- **Power handling, peak:** 1600W
- **Maximum SPL:** 125dB / 1m
- **Dimensions:** 29.5" x 43.9" x 11.9" (74.9cm x 111.5cm x 30.2cm)
Dimensioned drawings on next page.
- **Product weight, each:** 147 (66.7 kg)
- **Shipping weight, each:** ~158 (71.8 kg) w/o pallet

